



Paper No: 25PESGM0614

## State-of-Health Estimation for Lithium-ion Batteries via Ensemble Learning of Random Partial Discharging Curves

Dr. Yan Xu
Cham Tao Soon Professor in Engineering
Center for Power Engineering (CPE)
School of Electrical and Electronic Engineering
Nanyang Technological University
xuyan@ntu.edu.sg






# **Background**

- Widespread applications of Lithium-ion battery energy storage systems
- Battery degradation is inevitable, which leads to capacity and power decrease
- State-of-health (SOH) estimation is a crucial function of battery management system
- SOH is defined as the ratio of present capacity to the nominal capacity

$$SOH = \frac{C_{now}}{C_{nominal}} \times 100\%$$






Fu, Shiyi, et al. "Data-driven capacity estimation for lithium-ion batteries with feature matching based transfer learning method." Applied Energy 353 (2024): 121991.






## Introduction

Data-Driven methods for Lithium-ion battery SOH estimation



Challenges brought by random partial discharging curves



the discharging curve of each cycle starts and ends at random voltages, so it is **impossible** to **predefine a voltage window** that is consistently covered by all cycles for **HI extraction** 

### **Existing problems** of data-driven methods:

- Data-driven methods often extract HIs from predefined voltage windows, which fail during random partial discharging process
- Existing unscaled health indicator (HI) is sensitive to cell-to-cell variation

**Solution** – a new **ensemble learning** method is proposed

- Scaled HI is extracted to alleviate the negative impact of cell-to-cell variation on SOH estimation
- Multiple Gaussian process regression (GPR) based
   SOH estimator are constructed over different
   voltage windows
- SOH is estimated by aggregating estimators within actual discharging voltage range via product of experts (PoE) method





# Methodology


## Framework of the proposed method

### Offline stage:

- Collect complete discharging curves
- Split each curve into M segments
- Extract scaled HI from each segment
- Construct an individual GPR-based SOH estimator for each segment

### **Online stage:**

- Collect a random partial discharging curve
- Activate GPR models within the partial curve via segment-model matching
- Estimate SOH by aggregating activated GPR models via PoE







# Methodology

## Online ensemble-model fusion

### **Scaled HI extraction**

 $\Delta t_a$ 

 $\Delta t_{p}$ 

 $\Delta t_k$  p ... k

random partial discharging curve

voltage

 $HI_p = \Delta Q_p / \Delta Q_p^1$ ,  $\Delta Q_p = I \Delta t_p$ 

 $HI_k = \Delta Q_k / \Delta Q_k^1$ ,  $\Delta Q_k = I \Delta t_k$ 

 $HI_q = \Delta Q_q / \Delta Q_q^1$ ,  $\Delta Q_q = I \Delta t_q$ 

 $\Delta Q_i^1$  (i= p,...,q) is the charging

capacity  $\Delta Q_i$  at 1-th cycle

## Activate q-p+1 GPR models

 $HI_p$  p-th GPR:  $P(SOH|D_p) = \mathcal{N}(\mu_p, \sigma_p^2)$  $D_p$ : training data of p-th GPR

Estimated SOH:  $\mu_p$ 

Uncertainty:  $\sigma_p^2$ 

 $\{\mu_i\}_{i=p}^q$ 

 $\{\sigma_i^2\}_{i=p}^q$ 

k-th GPR:  $P(SOH|D_k) = \mathcal{N}(\mu_k, \sigma_k^2)$ 

 $D_k$ : training data of k-th GPR

Estimated SOH:  $\mu_k$ 

Uncertainty:  $\sigma_k^2$ 

 $HI_q$  q-th GPR:  $P(SOH|D_q) = \mathcal{N}(\mu_q, \sigma_q^2)$ 

 $D_a$ : training data of q-th GPR

Estimated SOH:  $\mu_a$ 

Uncertainty:  $\sigma_a^2$ 

### Aggregate q-p+1 GPR models

Product of experts (PoE):

$$P(SOH|D) = \prod_{i=n}^{q} P(SOH|D_i)$$

$$P(SOH|D) = \mathcal{N}(\mu, \sigma^2)$$

 $D = \{D_i\}_{i=n}^q$ : training data of

activated GPR models



Final SOH estimate:  $\mu = \sum_{i=n}^{q} w_i \mu_i$ 

Weight:  $w_i = \frac{\sigma_i^{-2}}{\sum_{i=n}^q \sigma_i^{-2}}$ 

Decrease the weights of SOH estimates with great uncertainty





# **Results**

## Case 1: comparison with $R^2$ based multi-model fusion

Table. 1 Comparison of mean RMSE across testing batteries

methods	Oxford data	NASA data				
proposed method	0.72%	1.25%				
${\it R}^{2}$ based multi-model fusion	1.10%	1.64%				


The proposed method achieves 35% and 24% lower mean RMSE on two datasets

### Case 2: comparison with unscaled HI

Table. 2 Comparison of **mean**, standard deviation (**std**), and **maximum** of RMSE across testing batteries

	Oxford data		NASA data			
methods	mean	std	max	mean	std	max
proposed HI	<b>0</b> . <b>72</b> %	0.29%	1.30%	1.25%	0.03%	1.28%
unscaled HI	0.91%	0.57%	1.91 %	2.16%	1.35%	3.71%

- The proposed HI achieves 21% and 42% lower mean RMSE on two datasets
- The proposed HI achieves more consistent estimation, demonstrated by smaller std and maximum of RMSE



SOH estimation results on Oxford dataset (a) and NASA dataset (b)





## **Conclusions**

### **Conclusions:**

- This paper proposes a new ensemble learning method to estimate SOH from random partial discharging curves.
- A scaled HI is proposed to effectively reduce the negative impact of cell-to-cell variation on SOH estimation.

### **Future work:**

 The future research aims to extend the proposed method to dynamic working conditions, necessitating extracting reliable HI from dynamic working conditions.

### Our related works:

- B. Gou, Y. Xu and X. Feng, "A Hybrid Data-Driven and Model-based Method for Modeling and Parameter Identification of Lithium-Ion Batteries," *IEEE Trans. Industry Applications*, 2023.
- G. Dong, Y. Xu, and Z. Wei, "A Hierarchical Approach for Finite-time H-∞ State Observer and Probabilistic Lifetime Prediction of Lithium-Ion Batteries," *IEEE Trans. Energy Conversion*, 2022.
- W. Liu and Y. Xu, "Data-Driven Online Health Estimation of Li-Ion Batteries Using A Novel Energy-Based Health Indicator," IEEE Trans. Energy Conversion, 2020.
- B. Gou, Y. Xu, et al, "State-of-Health Estimation and Remaining-Useful-Life Prediction for Lithium-ion Battery Using A Hybrid Data-driven Method," *IEEE Trans. Vehicular Technology*, 2020. - Web of Science highly cited paper
- B. Gou, Y. Xu, et al, "An Ensemble Learning-based Data-Driven Method for Online State-of-Health Estimation of Lithium-ion Batteries," *IEEE Trans. Transportation Electrification*, 2020.
- W. Liu, Y. Xu et al, "A Hierarchical and Flexible Data-Driven Method for Online State-Of-Health Estimation of Li-ion Battery", IEEE Trans. Vehicular Technology, 2020.
- 7. W. Q. T. Poh, Y. Xu, and R. T. P. Tan, "Data-driven estimation of li-ion battery health using a truncated time-based indicator and LSTM," *Proc. IEEE PES General Meeting, Orlando, FL, USA, Jul. 2023.*
- B. Gou, Y. Xu, et al "Remaining Useful Life Prediction for Lithium-ion Battery Using Ensemble Learning Method," Proc. IEEE PES General Meeting, Atlanta, US, Aug. 2019. – Best Paper Award
- W. Liu and Y. Xu, "A Comprehensive Review of Health Indicators of Li-ion Battery for Online State of Health Estimation," *IEEE EI2 Conference*, 2019.
- Y. Xu, B. Gou, "Ensemble-Based Reliable Machine Learning and Decision-Making Algorithm for Lithium-Ion Battery Health Monitoring", Technology Disclosure, TD 2018-275, 2018. – licensed to the industry.
- Y. Xu, Y. Yang, W. Liu, "Online SOH Estimation of LIB Under Dynamic Discharging Profiles," Technology Disclosure, TD/2021-132, 2021.
- Y. Xu, W. Liu, C. Ren, "Expanding SOH Estimation Model of LIB to Different Conditions Using Transfer Learning," Technology Disclosure, TD/2021-133, 2021.
- Y. Xu, G. Dong, "A Hierarchical Framework for Battery States Estimation And Lifetime Prediction," Technology Disclosure, TD/2021-134, 2021.





Stability & Optimization & Data-Analytics For MORDERN POWER SYSTEMS